

Tempus GSM Watch Mobile Dialler

Features: 8 programmable telephone numbers, 4 different trigger alarm messages, calls or sends message when triggered, fully programmable using mobile telephone, internal microphone to listen & monitor premises, microphone or input alarm trigger, emergency panic button, two independent trigger inputs, solid state relay output, configurable as two zone alarm panel.



Product Specification

Electrical Specification

Low voltage input	9-16Vdc
Current drain standby	20mA
Current drain alarm	750mA (Dialling)
Alarm trigger	2 X OV or 12Vdc
Output	1 X solid state relay 60V / 50mA

Technical Specification

Plastic housing material	ABS/PC
Dimensions Length	115mm X 72mm X 24mm
Weight	100g

Activation Triggers

- On board panic button
- Input triggers 2 available
- Internal microphone

European Standards

Conforms to European law (EU) Low Voltage Directives LVD 73/23/EEC (amended 93/68/EEC) and Electro-magnetic Compatibility (EMC) 89/336/EEC (Amended by 92/31/EEC and 93/68EEC) RoHS

Telephone Numbers

- 8 alarm telephone numbers
- 1 service telephone number
- 24 digits per telephone number

Dialling

- Call and/or sends message upon activation or alarm
- Up to 4 dial attempts per programmed telephone
- Up to 4 different messages

Network

- Quad band EGSM / GPRS
- 850/900/1800/1900Mhz

Order Number

LY69-001-67

Product Specification**Programmable Functions**

Change user code
Program/delete telephone numbers
Set number of dial attempts
Set call mode
Enable/disable trigger sources
Wattage Equivalent
Enable/disable call in
Set entry/exit time
Set microphone trigger level
Set retrigger level
Set microphone volume
Set up to 4 different alarm messages
Set service message
Set service message interval
Set output On/Off